

SPECIFICATIONS



For Earth, For Life
Kubota

Model		R430		
Type of ROPS / FOPS		CANOPY / CAB		
Engine	Model	D1803-CR-TIE4-WL6		
	Emission certification	Tier 4		
	Output (SAE J1995 gross)	HP (kW)/rpm	47.6 (35.5) / 2600	
	Output (SAE J1349 net)	HP (kW)/rpm	45.2 (33.7) / 2600	
	Displacement	cu.in. (cc)	111 (1826)	
Transmission	Type	Hydrostatic transmission		
Dimensions	Overall length	ft.in. (mm)	14' 4" (4355)	
	Overall height	ft.in. (mm)	8' 3" (2515)	
	Overall width (w/o bucket)	ft.in. (mm)	5' (1520)	
	Ground clearance	in. (mm)	11" (280)	
Auxiliary circuit	Auxiliary hydraulic flow	gpm (ℓ/min.)	11.1 (42.1)	
	Auxiliary hydraulic pressure	psi (Mpa)	2697 (18.6)	
Drive system	Tire size	12.5 / 70-16-8PR		
	Travel speed	Low / High	mph (km/h)	
	Max. traction force	lbs. (kN)	5485 (24.4)	
	Front axle traction lock	Limited slip differential		
	Articulation angle	deg.	40 (each direction)	
	Angle of rear frame oscillation	deg.	±8	
	Loader clearance circle	ft.in. (mm)	12' 1" (3695)	
	Turning radius track circle	ft.in. (mm)	10' 1" (3085)	
	Brakes	Service	Enclosed wet disc	
		Parking	Spring applied hydraulic released wet disc	
Lifting specifications	Tipping load (straight)	w/ bucket (ISO14397-1)	lbs. (kg)	
		w/ pallet forks (ISO14397-1)	lbs. (kg)	
	Tipping load (full turn)	w/ bucket (ISO14397-1)	lbs. (kg)	
		w/ pallet forks (ISO14397-1)	lbs. (kg)	
	Rated operating capacity (50% of tipping load)	w/ bucket (ISO14397-1)	lbs. (kg)	
		w/ pallet forks (ISO14397-1/SAE J1197)	lbs. (kg)	
Operational specifications	Standard bucket capacity	yd ³	0.5	
	Breakout force	lbs. (kN)	5215 (23.2)	
	Lifting capacity at ground level	lbs. (kN)	3687 (16.4)	
	Loader raise / lower time	sec.	4.4 / 3.3	
Fuel tank	gal. (ℓ)	14.3 (54)		
Hydraulic system	gal. (ℓ)	15.3 (58)		
Hydraulic reservoir	gal. (ℓ)	11.1 (42)		
Operating weight (Including operator weight @ 165 lbs.)	lbs. (kg)	7758 (3519) / 8232 (3734)		

R

KUBOTA WHEEL LOADER R430

Versatile and powerful, the R430 is also compact, letting you do jobs in places that bigger wheel loaders can't go.



Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.



KUBOTA TRACTOR CORPORATION

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: www.kubotausa.com

©2023 Kubota Corporation



**Kubota
Genuine Parts**
for maximum
performance,
durability and
safety

