


## Specifications

Model		U55-5		U55-5 Angle Blade	
Type of ROPS / FOPS		Canopy / Cab			
Type of tracks		Rubber, Steel		Rubber, Steel	
Engine	Model	V2607-CR-E5-BH1 / V2607-CR-E5-BH2			
	Output (SAE J1995 gross)	HP (kW) @ rpm	47.6 (35.5) @ 2200		
	Output (SAE J1349 net)	HP (kW) @ rpm	46.4 (34.6) / 45.5 (33.9) @ 2200		
	Displacement	cu. in. (cc)	159.6 (2615)		
Dimensions	Overall length	ft. in. (mm)	17'12" (5475)		
	Overall height	ft. in. (mm)	8'4" (2550)		
	Overall width	ft. in. (mm)	6'5" (1960)		
	Min. ground clearance	in. (mm)	12.2" (310)		
Hydraulic system	Pump capacity	GPM (ℓ/min)	14.8 (56.1) Variable × 2 / 9.8 (37.0) Gear × 1		
	Auxiliary hydraulic flow	AUX1 / AUX2 GPM (ℓ/min)	19.8 (75) / 9.8 (37)		
	Max. breakout force	Bucket / Arm lbs. (kgf)	10172 (4614) / 5869 (2662)		
Drive system	Travel speed	Low / High mph (km/h)	1.8 (2.8) / 3.1 (4.9)		
	Max. traction force	Low speed lbs. (kgf)	14480 (6567)		
	Tumbler distance	ft. in. (mm)	6'6" (1990)		
	Crawler length	ft. in. (mm)	8'2" (2500)		
	Shoe width	in. (mm)	15.7" (400)		
	Ground contact pressure	Rubber Canopy / Cab	psi (kgf/cm <sup>2</sup> )	4.6 (0.32) / 4.6 (0.33)	
		Steel Canopy / Cab	psi (kgf/cm <sup>2</sup> )	4.7 (0.33) / 4.7 (0.33)	
Swing system	Unit swing speed	rpm	9.2		
	Boom swing angle	Left / Right degree	70 / 55		
Blade	Dimensions	Width	ft. in. (mm)	6'5.2" (1960)	
		Height	ft. in. (mm)	16.1" (410) / 16.7" (425)	
	Max. lift above ground	in. (mm)	17.3" (440) / 20.1" (510)		
	Max. drop below ground	in. (mm)	15.9" (405) / 18.3" (465)		
	Angle	Left / Right degree	- / 25 / 25		
Hydraulic oil (Reservoir / System)		gal (ℓ)	11.1 (41.9) / 20.3 (77.0)		
Fuel reservoir		gal (ℓ)	17.4 (66.0)		
Operating weight (Including operator's weight @ 165 lbs.)	Rubber Canopy / Cab	lbs. (kgf)	12247 (5555) / 12456 (5650)		12721 (5770) / 12930 (5865)
	Steel Canopy / Cab	lbs. (kgf)	12533 (5685) / 12743 (5780)		13007 (5900) / 13217 (5995)

## Dimensions



Kubota Tractor Corporation reserves the right to change the stated specifications without notice. This brochure is for descriptive purposes only and reasonable efforts were used to set forth the contained information; some items shown may be optional and some products shown may not be available at all dealerships. Kubota disclaims all representations and warranties, express or implied, or any liability from the use of this brochure. For complete warranty, safety and product information, consult your local Kubota dealer and the operator's manual. Power (HP/KW) and other specifications are based on various standards or recommended practices. For your safety, Kubota strongly recommends the use of a Rollover Protective Structure (ROPS) and seat belt in almost all applications. This brochure is intended for the United States and US territories only. For information regarding Kubota products or services outside these areas, see Kubota Corporation's global web site. Kubota does not provide parts, warranty or service for any Product which is re-sold or retailed in any country other than the country for which the Product(s) were designed or manufactured.

# Kubota

**KUBOTA TRACTOR CORPORATION**

1000 Kubota Drive, Grapevine, TX 76051 Tel 888-4 KUBOTA

Visit our web site at: [www.kubotausa.com](http://www.kubotausa.com)

©2026 Kubota Corporation



**Kubota Genuine Parts**  
for maximum performance, durability and safety



For Earth, For Life

Kubota

# U

**KUBOTA TIGHT TAIL SWING COMPACT EXCAVATOR**

# U55-5

The next generation of tight tail swing compact excavators with advanced performance, comfort, and technology.

